

Smile Mini

SM.NN.000.OTA.FI



N° LED	w	Lm to the light source	-@-	00		R / V / B			
01	1.2	110	350mA	IP65	DIFFUSE	• • •	-	2700K 3000K 4000K	
Model		Description			Dimensions Ø48 x 58mm			Formwork for fixing Ø40 x 100mm	
ľ		Recessed wall/ceiling Led light body in aluminum, anti-blinding light with 45° emission. It is provided with 50 cm neoprene bipolar cable for the electrical connection. Finish: silver grey anodized, other finishes on request. Screen: transparent polycarbonate. Indoor/outdoor installation on any rigid surface by specific formwork. Pressure fixing by two O-ring OR, depth dimension 100mm.			<u>5.45</u> <u>47 + 11</u>			Ø 35 00 1 Ø 40	
Р	Position the for	mwork flush with the wall	Carry out the e	lectrical connection a	and insert the lighting body into the formwork Final result				
Series electrical connection 350mA SELV. POLARITY: Red CABLE + BLACK cable -						Connection: Connector compliant with EN 60998-2-1 standards			
					(FACSIMILE)				
ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.									
				ER SUPPLY LV OUTPUT 350mA constant current		ate waste collection ectric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy		
HI Pro	ject Srl Via	n Mario Luciani 4/E - 32032 Feltre (BL)	Tel. 0439 3	10098 <u>in</u>	<u>fo@hiproject.it</u>	<u>www.brillamenti</u>	. <u>it</u>	CF - PI e n. isc. reg. imprese 00967030255	