



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP40	DIFFUSE		-	2700K 3000K 4000K

Model	Description	Dimensions $\varnothing 48 \times 41\text{mm}$	Fixing hole $\varnothing 35\text{mm}$
	<p>Recessed wall/ceiling Led light body in aluminum, anti-blinding light with 45° emission. It is provided with 50cm neoprene bipolar cable for the electrical connection.</p> <p>Indoor installation on any rigid surface.</p> <p>Fixing by torsion springs, depth dimension 50mm.</p> <p>FINISH: BLACK / GREY ANODIZED ALUMINUM – GALVANIZED NICKEL – CUSTOMIZED RAL VARNISHED</p> <p>SCREEN: TRANSPARENT POLYCARBONATE</p>		

Series electrical connection 350mA SELV.	Polarity: Red cable + Black cable -	Connection: connector compliant with EN 60998-2-1 standards

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

Compliant with European standards <small>(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</small>	CLASSE III <small>Operating with SELV</small>	POWER SUPPLY <small>By remote power supply SELV OUTPUT 350mA constant current</small>	<small>Separate waste collection of electric and electronic equipment</small>	Made in Italy <small>Projected, manufactured and assembled in Italy</small>
---	---	---	---	---