



N° LED	W	Lm to the light source				R / V / B		
03	3.6	330	350mA	IP65	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø88 x 58mm	Formwork for fixing Ø85 x 80mm
	Recessed wall/ceiling Led light body in aluminum, anti-blinding light with 45° emission. It is provided with 50cm neoprene bipolar cable for the electrical connection. Finish: silver grey anodized, other finishes on request. Screen: opal polycarbonate. Indoor/outdoor installation on any rigid surface by specific formwork. Pressure fixing by two O-ring OR, depth dimension 80mm.		

Position the formwork flush with the wall	Carry out the electrical connection and insert the lighting body into the formwork	Final result

Series electrical connection 350mA SELV. POLARITY: Red CABLE + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards
	 IP68 connector for example Steab Paguro 5664 or similar

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--