



N° LED	W	Lm to the light source				R / V / B		
03	3.6	330	350mA/24V	IP65	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø88 x 58mm	Fixing formwork Ø85 x 80mm
	<p>Recessed wall/ceiling Led light body in aluminum, anti-blinding light with 45° emission. It is provided with 50cm neoprene bipolar cable for the electrical connection.</p> <p>Indoor/outdoor installation on any rigid surface by specific formworks.</p> <p>Pressure fixing by snap ring, depth dimension 100mm.</p> <p>FINISH: BLACK / GREY ANODIZED ALUMINUM – GALVANIZED NICKEL – CUSTOMIZED RAL VARNISHED</p> <p>SCREEN: OPAL POLYCARBONATE</p>		

<p><b>Series electrical connection 350mA SELV.</b> Polarity: <b>Red cable + Black cable -</b></p>	<p><b>Parallel electrical connection 12V / 24V.</b> Polarity: <b>Red cable + Black cable -</b></p>	<p><b>Connection to be made in a watertight place:</b> connector compliant with EN 60998-2-1 standards (FACSIMILE)</p> <p>IP68 connector for example Steab Paguro 5664 or similar</p>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASSE III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current/ By remote power supply SELV OUTPUT 24V constant voltage</p>	<p> Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	--	---	--	--