



N° LED	W	Lm to the light source				R / V / B		
18	7.3	532	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Define the position and drill in vertical axis	Fix to the wall Carry out the electrical connection	Dimensions
	On-wall Led lamp in aluminum and methacrylate, indirect light, directable diffusor. Finish: white RAL 9016 color the frame, the screen is white in the reflecting part, the outer part is available in four colors. Other colors on request. It is provided with 1m cable for the electrical connection by power supply. Indoor wall installation with two screws suitable to the support, not supplied by us.			 250x250x220

Screen color of the external part

RAL 6034		RAL 7022		GOLD		NEUTRAL	
----------	--	----------	--	------	--	---------	--

Parallel electrical connection 24V - Polarity: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards (FACSIMILE)

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

Compliant with European standards <small>(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</small>	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 24V constant voltage	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
---	---	--	--	--