



N° LED/mt	W/mt	Lm/mt alla sorgente luminosa				R / V / B		
480	40	2700	24V	IP20	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Define the position of the suspension. Carry out the electrical connection respecting the polarity.	On the steel cable define the height of the suspension from the ceiling, then adjust the length of the power cable and fix the rosettes to the ceiling with the screws.	Final result
	<p>Ceiling hanging Led light body in aluminum and methacrylate. Finish: metallic parts black varnished. Other colors/finishes on request. Screen: white opal methacrylate. It is provided with: 2m cable covered in fabric (available colors: black or red) for the connection to the power grid 24V, steel cable for the suspension.</p> <p>Indoor installation on any rigid surface. Assembly with two rosettes, fixing with four visible screws suitable to the support, not supplied by us. Maximum length of the lamp 2000mm.</p>			

Parallel electrical connection 24V. Polarity: Red cable + Black cable -	Connection: connector compliant with EN 60998-2-1 standards
	(FACSIMILE)

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged..

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 24Volt constant voltage		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	---	--	--	--