



cilindretto mini




Photo © Brillamenti Officina della Luce



Photo © Matteo Guidetti

Cilindretto Mini

CI.NN.040.OTA.FI




N° LED	W	Lm ca				R / V / B	
01	1,2	110	350mA	IP40	DIFFUSE - 7° - 25° - 40°	-	2700K 3000K 4000K

Aluminum Led body light for ceiling hanging.
It is provided with 2m black carrying cable 4mm diameter for the electrical connection.
Indoor installation on any rigid surface.
Fixing by two screws with specific rosette.
FINISH: WHITE RAL 9016 VARNISHED ALUMINUM - CUSTOMIZED RAL
SCREEN: TRANSPARENT POLYCARBONATE
*** Accessories: see page 132**

Cilindretto Mini

CI.NN.060.OTA.FI



N° LED	W	Lm ca				R / V / B	
03	3,6	330	350mA	IP40	DIFFUSE - 7° - 25° - 40°	-	2700K 3000K 4000K

Aluminum Led body light for ceiling hanging.
It is provided with 2m black carrying cable 4mm diameter for the electrical connection.
Indoor installation on any rigid surface.
Fixing by two screws with specific rosette.
FINISH: WHITE RAL 9016 VARNISHED ALUMINUM - CUSTOMIZED RAL
SCREEN: TRANSPARENT POLYCARBONATE
*** Accessories: see page 132**