



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP40	7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø20 x350 mm	Rosette Ø50x2mm	Rosette Ø20mm
	Aluminum Led body light for ceiling hanging. Finish: white RAL 9016 varnished, customized RAL, other materials on request. Single emission, transparent polycarbonate screen. It is provided with 2m black carrying cable 4mm diameter for the electrical connection. Indoor installation on any rigid surface. Fixing by two screws with specific rosette			

With rosette Ø50x2mm			With rosette Ø20mm		
Define the length of the suspension and fix the cable stopper by screwing the screw.	Carry out the electrical connection	Fix the rosette by screws with maximum diameter 4mm	Fix the rosette by screws with maximum diameter 4mm	Define the length of the suspension, fix the cable stopper by screwing the screw and do the electrical connection	Screw the socket to the rosette

Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--