



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP40	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø20 x350 mm	Fixing support Ø50x2mm
	<p>Aluminum Led body light for ceiling hanging. Single emission, transparent polycarbonate screen.</p> <p>It is provided with 2m black carrying cable 4mm diameter for the electrical connection. Indoor installation on any rigid surface. Fixing by two screws with specific rosette.</p>		

<p>Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

	<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current</p>	<p> Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	--	---	--	--	--