



N° LED/mt	W/mt	Lm/mt In the illuminating part				R / V / B		
200	23	5800	24V	IP40	DIFFUSE	-	-	- 3000K 4000K

Model	Description	Dimensions 2160 x235 x21 mm
	On-wall/ceiling Led light body in white Corian® and aluminum in the not visible part. Curvilinear aesthetics shape. Finish: opaque white in view. It is provided with 1m bipolar cable for the electrical connection, positioning jig and supports for the fixing. Indoor installation, assembly by two magnets fixed with countersunk head screws 4mm diameter. Easy positioning thanks to the reference jig.	

**Reference jig for drilling**

Define the lamp position. Arrange the jig to the wall/ceiling to define position of the electricity supply hole and of the two magnets.

**Magnets fixing**

**ATTENTION! THE MAGNET MUST NOT BE RECESSED WITH RESPECT TO THE FLUSH OF THE LAMP SUPPORT SURFACE**

Fix the magnets with countersunk screws 4Ømm.

**Electrical connection and fixing the led lighting body**

Connect the power cables to the lamp, align and place the lamp supports in the magnets positions.

Parallel electrical connection 24V: Polarity: **RED cable + BLACK cable -**

**Connection:** Connettor compliant with EN 60998-2-1 standards

(FACSIMILE)

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant to the European legislations</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SOURCE</b> By remote power supply SELV OUTPUT 24V constant voltage		SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	---	---	---	--	---	---