



| N° LED | W | Lm to the light source | | | | R / V / B | | |
|--------|-----|---------------------------|-------|------|----------------|-----------|-----|-------------------|
| 01 | 1.2 | 110 | 350mA | IP67 | 7° - 25° - 40° | | - | 2700K 3000K 4000K |
| 01 | 3.6 | - | 350mA | IP67 | DIFFUSA - 40° | - | RGB | - - - |

| Model | Description | Dimensions Ø40 x 70mm | Formwork for fixing: inner Ø32mm exterior Ø36mm x 100mm |
|-------|--|-----------------------|--|
| | Recessed floor Led light body in stainless steel. It is provided with 50cm neoprene cable for the electrical connection. Finish: stainless steel in view, screen: thick transparent polycarbonate. Indoor/outdoor installation on the floor with specific formwork. Pressure fixing with compression springs and/or OR, depth dimension 90mm. | | |

| | | | | |
|---|--|--|-----------------------|---------------|
| NO | NO | YES | | |
| The formwork must not be higher than the finished floor | The formwork must not be lower than the finished floor | The formwork must be flush with the finished floor | Electrical connection | Finished work |

| | |
|---|--|
| Series electrical connection 350mA SELV. Polarity: Red cable + Black cable - | Connection: connector compliant with EN 60998-2-1 standards (FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar |
| | |

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

| | | | | | | |
|--|--|---|--|--|--|--|
| | Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD)) | CLASS III Operating with SELV | POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current | | Separate waste collection of electric and electronic equipment | Made in Italy Projected, manufactured and assembled in Italy |
|--|--|---|--|--|--|--|