



N° LED	W	Lm to the light source				R / V / B		
03	10,5	--	350mA	IP65	DIFFUSE - 40°	-	RGB	- - -
01	6,3	742	350mA	IP65	25°- 35°- 50°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø99 x 50 mm	Formwork for fixing Ø80 x 78.8mm
	Recessed floor Led light body in stainless steel. Finish: stainless steel, screen: thick opal/transparent polycarbonate. It is provided with 50cm neoprene cable (on request also different lengths) for the electrical connection. Indoor/outdoor installation on the floor with specific formwork. Pressure fixing with OR, depth dimension 80mm.		

RECOMMENDED: Place a plastic tube with a 110 diameter where the spotlight will be recessed	RECOMMENDED: Cut the tube at the same level of the flooring support surface	Drill the floor (85 mm diameter) to the predetermined size	In the floor, insert and glue with silicone the formwork	Connect the spotlight to the electrical system	Spread a thin layer of oil in the formwork and insert the spotlight.

Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -	Connection: Connector compliant with EN 60998-2-1 standards <i>(FACSIMILE)</i>	ONLY FOR 350mA RGB VERSION Connection to the pilot module
	 IP68 connector for example Steab Paguro 5664 or similar	+ = red - = red/black + = blue - = blue/black + = green - = green/black

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current / Only for 350mA RGB version, please see the connection to the pilot module	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--