

Porto Rotondo

PO.NN.000.OTA.FI



N° LED	W	V Lm to the light source		-A-	00	$\mathbf{\nabla}$	R / V / B					
03	3.6	330		350mA	IP65	DIFFUSE	• • •	-	2700K	3000K	4000K	
Model	Description		Dimensions 120 X 60 x 770mm		INSTALLATION							
	Floor stainless steel Led light body with light emission inclined 45 ° downwards. Finish: satinized stainless steel, other finishes on request. Screen: transparent polycarbonate. It is provided with 1m neoprene bipolar cable for the electrical connection. Outdoor installation on any rigid plane surface. Lamp assembly to the support by two screws supplied by us.											
						e floor by two screws ied by us.	Assemble the light body to the support by two screws supplied by us.		Final result			
Series electrical connection 350mA SELV. POLARITY : RED cable + BLACK cable -							Connection: Connector compliant with EN 60998-2-1 standards					
							(FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar					
	ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.											

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged. Separate waste collection **Compliant with European standards** CLASS III POWER SUPPLY Made in Italy $\overline{\mathbf{x}}$ CE of electric and electronic (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive Operating with SELV By remote power supply SELV OUTPUT 350mA constant current Projected, manufactured and assembled in Italy equipment (LVD) HI Project Srl Via Mario Luciani 4/E - 32032 Feltre (BL) Tel. 0439 310098 info@hiproject.it www.brillamenti.it CF - PI e n. isc. reg. imprese 00967030255