



| | | | | | | | | |
|--------|-----|---------------------------|-------|------|-----|-----------|---|-------------------|
| N° LED | W | Lm to the light source | | | | R / V / B | | |
| 02 | 2.4 | 220 | 350mA | IP65 | 40° | | - | 2700K 3000K 4000K |

| Model | Description | Assembly | | | Dimensions 180 x 180 x 700mm |
|-------|--|--------------------|-----------------------|--------------------------|------------------------------|
| | Floor Led light body in stainless steel and wood, with light emission inclined 45 ° downwards. Finish: untreated larch and satinized stainless steel, other finishes on request. It is provided with 1m neoprene bipolar cable for the electrical connection. IP65 in the illuminating part. Outdoor installation on any rigid draining surface. Fixing by four screws not supplied by us. | | | | |
| | | Fixing to the base | Electrical connection | Led lighting body fixing | |

| | |
|---|--|
| Series electrical connection 350mA SELV. Polarity: Red cable + Black cable - | IP68 connector for example Steab Paguro 5664 or similar. Connector compliant with EN 60998-2-1 standards |
| | Connection to be made in a watertight place |

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

| | | | | |
|--|---|--|--|--|
| Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD)) | CLASS III Operating with SELV | POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current | Separate waste collection of electric and electronic equipment | Made in Italy Projected, manufactured and assembled in Italy |
|--|---|--|--|--|