







N° LED / mt	W / mt	Lm to the light source				R / V / B		
128	23	3100	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Descrizione	Dimensions Ø1300x80mm
	<p>Ceiling hanging Led light body, aluminum and wood frame. Circle diameter 1300mm. It is provided with 2m white grey color streaked bipolar cable for the electrical connection. Indoor installation on any rigid surface with special steel cables. Assembly with rapid hooking fixed on the ceiling by screws not supplied by us.</p>	 <p>Ø1300x80mm</p>

<p><b>Parallel electrical connection 12V / 24V</b>    <b>Polarity: Red cable + Black cable -</b></p> 	<p><b>Connection:</b> connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p> 
---	--

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASSE III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	--	---	--