



N° LED / mt	W / mt	Lm to the light source				R / V / B		
128	23	3100	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø700x80mm
	<p>Ceiling hanging Led light body, aluminum and wood frame. Circle diameter 700mm.</p> <p>It is provided with 2m white grey color streaked bipolar cable for the electrical connection.</p> <p>Indoor installation on any rigid surface with special steel cables.</p> <p>Assembly with rapid hooking fixed on the ceiling by screws not supplied by us.</p>	<p>Ø700x80mm</p>

<p><b>Parallel electrical connection 12V / 24V</b>    Polarity: <b>Red cable +</b>    <b>Black cable -</b></p>	<p><b>Connection:</b> connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
----------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASSE III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------	----------------------------------------------------------------------------------------	-----------------------------------------------------------------------	--------------------------------------------------------------------------------