

N° LED	W	Lm to the light source				R / V / B			2700K	3000K	4000K
01	1.2	110	350mA	IP65	DIFFUSE	-	-		2700K	3000K	4000K

Model	Description	Floor version Ø27 x 46mm	Fixing formwork for floor version Ø25 x 60mm	Ceiling version Ø27 x 46mm
	<p>Recessed, ceiling, wall and floor Led light body in stainless steel. Finish: stainless steel, screen: thick transparent polycarbonate. It is provided with 25 cm neoprene bipolar cable for the electrical connection.</p> <p>Floor/ceiling/wall installation, with specific formwork or with compression springs. Pressure fixing with OR on the formwork or on the diameter compartment 22 mm without formwork and with compression springs. Depth dimension 80mm.</p>			

<p>NO</p> <p>1) Insert the formwork and glue it flush with the floor</p>	<p>YES</p> <p>2) Carry out the electrical connection</p>	<p>3) Insert the spotlight in the formwork</p>	<p>Drywall</p> <p>Hole Ø22mm</p>
---	---	--	--

<p>Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -</p>	<p>IP68 connector for example Steab Paguro 5664 or similar: Compliant with EN 60998-2-1 standards</p>	<p>Connector: Compliant with EN 60998-2-1 standards</p>
	<p>(FACSIMILE)</p> <p>Connection to be made in a watertight place</p>	<p>(FACSIMILE)</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	---	--	---	--