



N° LED	W	Lm to the light source				R / V / B		
↑03 ↓03	7.2	660	350mA	IP65	7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø80x160mm
	On-wall aluminum Led light body. Finish: black varnished, other colors on request. Diffuser screen: transparent polycarbonate. IP65 protection degree in the lighting part. It is provided with 25cm bipolar cable for the electrical connection. On-wall indoor /outdoor installation on any rigid surface. Fixing by two screws not supplied by us.	 Ø80x160

Place the support and drill with a tip 5 mm maximum diameter	Fix the support to the wall	Carry out the electrical connection of the Led lighting body and fix it to the support	Final result

<b>Series electrical connection 350mA SELV. POLARITY: RED cable + BLACK cable -</b>	<b>Connection:</b> Connector compliant with EN 60998-2-1 standards
	(FACSIMILE) 

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	---	--	--	--