




EL.NN.000.OTA.FI



N°LED/m	w	W/m	Lm to the light source	Lm/m to the light source	Luminous efficiency	Chromatic deviation	CRI	OO IP65 to the light source	$\mathbf{\nabla}$	R / V / B	٩	
128	4,6	23	720	- 3600 -	>150Lm W	SDCM 3	> 80	total protection against dust, protection against water splashes	Diffuse	-	-	2700К – 3000К – 4000К

*The above data refer to a temperature of 3000K

Model	Description	Dimensions 360 x 225 x 120 mm
	On-ground Led light body in stainless steel. Finish: varnished faux corten steel, other colors on request. Screen: sandblasted polycarbonate. It is provided with 50cm neoprene bipolar cable for the electrical connection. Indoor/outdoor installation, resting on a flat surface, fixing by four screws not supplied by us.	





INSTALLATION AND USE MANUAL

Assembly Assembly to the support using screws with a maximum diameter of 8mm. PAY ATTENTION TO THE CABLES POLARITY DURING THE ELECTRICAL CONNECTION WARNING AND PROVISIONS ATTENTION! 128 led/m The appliance safety is guaranteed only by respecting, both during installation and employment phase, of the following instructions. It is therefore necessary to archive the present 23W/m 3000°K document. WARNINGS: ENERG⁴ • The power supply voltage must be removed during the installation and during any operation. • The appliance must not be modified or tampered with in any way. Every modification can compromise the safety of the appliance, making it dangerous. NECTO GROUP SRL Hi. Project srl refuses any responsibility for modified or tampered with products. Modifications or tampering with the product, if not authorized by the company (Hi. Project s.r.l.), nullify 3SLEHFAWW6402E05 any direct and indirect responsibility of the manufacturer as well as the warranty. • The appliance is free from the photobiological risk. Please follow the instructions of this data sheet. • The product is to be considered a "Containing Product" and is not subject to maintenance. The light source can only be replaced by the manufacturer. For further information please contact Hi.Project s.r.l. • If the flexible power cable is damaged, it can be substituted only by the manufacturer. For further information please contact Hi.Project s.r.l. • Each product, at the end of its life, must be committed to a waste storage center specialized in electrical and electronic equipment. Alternatively, it can be returned to the D manufacturer. WARRANTY CONDITIONS: Our products are guaranteed for 24 months from the date of purchase. The warranty only covers construction defects attributable to the manufacturer. The warranty does not include all the activities necessary for the product to arrive free port at the manufacturer for repair. The warranty is void if the malfunction is due to: improper use of the product, tampering, repairs not authorized by Hi. Project S.r.l., negligence of the installer, failure to comply with the product rating plate, damage due to natural causes such as lightning or power surges, use of power supplies or drivers not approved by Hi. Project S.r.I. and/or in any case not compliant **2** kWh/1000h with the technical regulations that regulate the European market, damage caused by wrong connections or connections with an IP degree lower than the purchased product, damage caused during the transport (even if the transport is organized by Hi. Project S.r.I. on behalf of the Customer), other causes that are not expressly and unequivocally referred to the defectiveness of the product itself. PRODUCT CLEANING INSTRUCTIONS • To clean the appliance, use exclusively a soft cloth, possibly moistened with water and neutral soap. • Warning: do not use aggressive cleansers, alcohol or solvents. The information contained in this document may be changed by Hi. Project s.r.l. at any time without notice and does not imply the assumption, even implicit, of any obligation on the part of Hi. Project Srl. Hi. Project Srl refuses all responsibility if the installation is not carried out by gualified personnel and in compliance with current regulations.