

Elle

EL.NN.000.OTA.FI



N° LED/mt	W/mt	Lm/mt to the light source	-A-	00	$\mathbf{\nabla}$	R / V / B				-
128	4	450	24V	IP65 in the illuminating part	DIFFUSE	-	-	2700K	3000K	4000K

Model	Description	Assembly	Dimensions 400 x 200 x 120 mm		
	On-ground Led light body in stainless steel. Finish: varnished faux corten steel, other colors on request. Screen: sandblasted polycarbonate. It is provided with 50cm neoprene bipolar cable for the electrical connection. Outdoor installation, resting on a flat surface, fixing by four screws not supplied by us.	Image: the electrical connection and fix with plugs for screws maximum diameter 8mm.	400 200 200		

Parallel electrical connection 24V Polarity: RED cable + BLACK cable - 					Connection: Connector compliant with EN 60998-2-1			
CE	Compliant to the European legislations (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD)	CLASS III Operating with SELV	POWER SOURCE By remote power supply SELV OUTPUT 24V constant voltage	X	SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT	Made in Italy Projected, manufactured and assembled in Italy		
HI Project Srl	Via Mario Luciani 4/E - 32032 Feltre (BL) Tel. 0439 310	098 <u>int</u>	fo@hiproject.itwww	.brillamenti.it	CF - PI e n. isc. re	eg. imprese 00967030255		