

Elle

EL.NN.020.OTA.FI




N° LED/mt	W/mt	Lm/mt to the light source	- A-	٥٥	7	R/V/B				
128	4	450	24V	IP65 in the illuminating part	DIFFUSE	-	-	2700K	3000K	4000K

Model


Description

On-ground Led light body in stainless steel. Finish: varnished faux corten steel, other colors on request. Screen: sandblasted polycarbonate. It is provided with 50cm neoprene bipolar cable for the electrical connection. Outdoor installation, resting on a flat and vertical surface, fixing by two screws not supplied by us.




Do the electrical connection and fix with plugs for screws maximum diameter 8mm.

Dimensions 360 x 300x 80 mm



Parallel electrical connection 24V

Polarity: RED cable + BLACK cable -



Connection: Connector compliant with EN 60998-2-1



IP68 connector for example Steab Paguro 5664 or similar

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

 ϵ

Compliant to the European legislations

(EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD)

CLASS III

Operating with SELV

POWER SOURCE

By remote power supply SELV OUTPUT 24V constant voltage



SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT

Made in Italy
Projected, manufactured and

ojected, manufactured and assembled in Italy