

KAKTUS

KK.NN.000.OTA.FI



Designer Maurizio Longo

N° LED	w	Lm to the light source	Luminous efficiency	Chromatic deviation	CRI			R / V / B	٩	
03+03	3.6+3.6	330+330	>92Lm W	SDCM 2	> 80	total protection against the dust protected against the ingress of liquids	7° - 25° - 40°	-	-	2700К – 3000К – 4000К

*The above data refer to a temperature of 3000K

MODEL	DESCRIPTION	DIMENSIONS
	Indoor/outdoor Led light body in stainless steel and aluminum with two adjustable Led floodlights. It is provided with two bipolar power supply cable in neoprene, length 1 meter, for the electrical connection. Finish: "faux Corten" varnished, other colors on request. Screen: transparent polycarbonate. The IP65 protection degree is to be understood on the two light sources. Installation on any rigid and flat surface. Fixing by four screws suitable to the support base, not supplied by us. In order to make sure a good functioning and a long lasting of the product the electrical connections must be made in a watertight environment.	009 009 00 00 00 00 00 00 00 00 00 00 00

ECTRICITY SUPPLY: 350mA constant current SELV POWER SUPPLY, not included, remotely placed.	Connection: Connector compliant withEN 60998-2-1							
Series electrical connection. POLARITY: RED Cable + BLACK Cable- // BROWN Cable + light blue CABLE -	ATTENTION The protection degree of the connection system must be identical or greater than the protection degree of the product. The junction clips are not included. The installation must be carried out by qualified personnel.	IP68 connection for outdoor use: (FACSIMILE)						
• ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. The connection to the electricity grid must be carried out only after completing the wiring of all the components. If this simply rule is not respected, the lighting source will be irremediably damaged. The installation must be carried out by qualified personnel.								
Compliant with European standards	PERATURE Separate waste collection of electr	Made in Italy						

C C Compliant with Euro EMC – RoHS – REA			It must not be provided with a electrical ground of protection	DIMMABLE By dimmable power supply	OPERATING TEMPERATURE -20°C +40°C	X	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
HI Project Srl	Via Mario Luci	ani 4/E -	32032 Feltre (BL)	Tel. 0439 310098	info@hiproject.it	w	ww.brillamenti.it CF - PI	e n. isc. reg. imprese 00967030255



INSTALLATION AND USE MANUAL

	INSTALLATION			
PREPARE THE SUPPORT PLANE	CARRY OUT THE ELECTRICAL CONNECTION AND FIX THE LIGHT BODY	ADJUST THE FLOODLIGHTS	FINAL RESULT	
FIX THE SUPPORT				
	WARNING AND PROVISIONS		<u> </u>	
 present document. WARNINGS: The power supply voltage must be removed during the The appliance must not be modified or tampered with Hi.Project srl refuses any responsibility for modified or s.r.l.), nullify any direct and indirect responsibility of the The appliance is free from the photobiological risk. P The product is to be considered a "Containing Product information please contact Hi.Project s.r.l. If the flexible power cable is damaged, it can be substended to the product, at the end of its life, must be committed manufacturer. WARRANTY CONDITIONS: Our products are guaranteed for 24 months from the const include all the activities necessary for the product of the warranty is void if the malfunction is due to: improcemply with the product rating plate, damage due to mand/or in any case not compliant with the technical reglower than the purchased product, damage caused durare not expressly and unequivocally referred to the detail to the detail	th in any way. Every modification can compromise the safety of tampered with products. Modifications or tampering with the emanufacturer as well as the warranty. lease follow the instructions of this data sheet. ct" and is not subject to maintenance. The light source can onl tituted only by the manufacturer. For further information plea ed to a waste storage center specialized in electrical and electr date of purchase. The warranty only covers construction defect to arrive free port at the manufacturer for repair. oper use of the product, tampering, repairs not authorized by hatural causes such as lightning or power surges, use of power gulations that regulate the European market, damage caused I ring the transport (even if the transport is organized by Hi. Pro	f the appliance, making it dangerous. product, if not authorized by the company (Hi.Project y be replaced by the manufacturer. For further se contact Hi.Project s.r.l. onic equipment. Alternatively, it can be returned to the ts attributable to the manufacturer. The warranty does Hi. Project S.r.l., negligence of the installer, failure to supplies or drivers not approved by Hi. Project S.r.l. by wrong connections or connections with an IP degree	3000°K Entity Elettronica S.r.I. 1200EN0786-930-0-XPE2M00 A B C D E F G C C D E F G C C D E F G C C D E F G C C D D E F G C C D D E C C D D E C C D D E C C D D E C C D D E C D D E C D D E C D D E C D D E C D D E C D D E C D D E E E C D D E E E E E E E E E E E E E	
obligation on the part of Hi. Project Srl.				