

N° LED double emission	W	Lm to the light source				R / V / B		
07	8.4	770	350mA	IP40	Diffused and downwards directed light	-	-	2700K 3000K 4000K
01	9	1060	500mA	IP40	Diffused and downwards directed light	-	-	2700K 3000K 4000K

Model	Description		Dimensions Ø60 x 155mm
	<p>On-ceiling Led light body in aluminum. It is provided with 25cm bipolar cable for the electrical connection. Finish: metal part white Ral 9016 varnished, other colors, finishes on request. Indoor installation, fixing with two countersunk screws Ø4mm suitable for the fixing support, not supplied by us.</p>		
Define the position	Fix the metal support to the ceiling with two countersunk screws Ø4 mm	Carry out the electrical connection respecting the polarity and screw the diffuser component	Final result

<p><b>Series electrical connection 350mA/500mA SELV. POLARITY: RED cable + BLACK cable -</b></p>	<p><b>Connection:</b> Connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
--	--

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p><b>CE</b> Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASS III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current</p>	<p> Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
---	---	--	--	--