

N° LED	W	Lm / metro to the light source				R / V / B		
128	23	3200	24Vdc	IP20	DIFFUSE	-	-	2700K 3000K 4000K
060	15	-	24Vdc	IP20	DIFFUSE	-	RGB	- - -

Model	Description	Dimensions Ø 40 x L	Housing seat
	Recessed wall/ceiling Led light body in aluminum and polycarbonate. Protruding tubular diffusor. Visible finish of the tubular: opal white. Tubular diffusor: opal white. It is provided with 25cm bipolar cable for the electrical connection. Maximum length 1200mm. Indoor installation on a drywall. Fixing with torsion springs on a 23mm compartment, depth 30mm.		

Carry out the housing seat of the bar	Carry out the electrical connection respecting the polarity and insert in seat the lamp	Final result

<p>Parallel electrical connection 24Vdc. Polarity: Red cable + Black cable -</p>	<p>ONLY FOR 24V RGB Connection to the pilot module</p> <p>Negative = red Negative = blue Negative = green Positive = black</p>	<p>Connection: connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
--	--	--

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 24Vdc constant voltage / Only for 24Vdc RGB version, please see the connection to the pilot module		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	----------------------------------	--	--	--	---