



N° LED	W	Lm to the light source				R / V / B		
01	6,5 - 9	750 - 1060	350mA - 500mA	IP 40	50°	-	-	2700K 3000K 4000K

Model	Description	Wall lamp fixing with two countersunk screws Ø4mm Electrical connection	Dimensions Ø60 x 90 mm
	<p>Product name: ARCO. LED wall lamp in aluminum. Standard finish: the aluminum cylinder grey anodized, the curved bracket black varnished, other colors on request. Opal white polycarbonate diffuser screen in perfect continuity with the cylinder diameter.</p> <p>The diffuser screen allows to have, in addition to the direct light downwards, also a diffused environment lighting. Maximum dimensions: 165mm x 230mm. It is provided with neoprene cable covered by black/red/grey tissue, for the electrical connection to the remote power supply. IP40 protection degree. Indoor installation on any flat and rigid surface.</p> <p>Fixing by two screws suitable to the support not supplied by us.</p>		

<p>Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE) Indoor connector</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA/500mA constant current</p>	<p> Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	--	---	--	--	--